

LiFePO4 Lithium Battery LPR24V400H 25.6V 400Ah



LPR Series Brief Introduce

LPR Series 19' Rack Mounted Rechargeable LiFePO4 Lithium Battery is a safety and reliable solution for providing energy storage in industrial applications such as data centers and telecom base stations. Low voltage offer multiple nominal voltages (12.8V/25.6V/38.4V/48.0V/51.2V etc.). With its high energy density, fast recharge time and compact design, this battery provides a highly efficient and cost-effective energy storage option for a range of applications in the industry. The 19-inch standard Rack Mount Lithium Battery is easy to install, scalable, space-efficient, and compatible with other equipment. It's popular in Lithium Solar Batteries system, Home Solar Energy storage system and SME (Small Medium Enterprise).

Long
Life

Lithium Iron
Phosphate




Deep
Cycle



Applications

- BTS Stations, Telecom System
- Internet data center(IDC)
- Solar Energy/Off-Grid System
- Access net work system
- UPS System, EPS System
- Terminal of FTTX
- Indoor distribution system

Dimensions & Weight



Technical Specifications

- Length: 420±1mm Width: 442±1mm Height: 266±1mm
- Weight: 79.0±0.1kgs

Electrical Characteristics	Nominal Voltage	25.6V
	Nominal Capacity	400Ah
	Energy	10240Wh
	BMS with internal cell balancing	YES
	Cycle Life	≥6000cycles @ 80%DOD
	Months Self Discharge	<3%
	Efficiency of Charge	100%@0.2C
	Efficiency of Discharge	96~99%@0.5C
Standard Charge	Charge Voltage	28.8V±0.2
	Charge Mode	0.5C to 28.8V, then 28.8V, charge current to 0.02C(CC/CV)
	Charge Current	50A
	Max. Charge Current	100A
	Charge Cut-off Voltage	28.8V±0.2
Standard Discharge	Continuous Current	50A
	Max continuous discharge current	100A
	Discharge Cut-off Voltage	21.6V±0.1
Environmental	Charge Temperature	0℃ to 45℃ (32F to 113F) @60±25% Relative Humidity
	Discharge Temperature	-20℃ to 60℃ (-4F to 140F) @60±25% Relative Humidity
	Storage Temperature	0℃ to 40℃ (32F to 104F) @60±25% Relative Humidity
	Water Dust Resistance	IP21
Mechanical	Cell & Method	Prismatic Cell 3.2V100Ah, 8S4P
	Case	Iron
	Dimensions (in./mm.)	442*420*266mm/17.41*16.54*10.48Ins
	Weight (lbs./kg.)	Approx: 79kgs/174.14lbs
	Gravimetric specific energy	129.62WH/KG
	Protocol (optional)	ModBus: CAN/RS485/RS232(OPT)
	SOC (optional)	LCD

Inverters Support Brands: GROWATT solis PYLONTECH MEGAREVO STUDEY Voltronic Power MUST美世乐 victtron energy GOODWE

SACOLAR KSTAR科士达 invt英威腾 Schneider Electric Deye德业 IYANG SOFAR SOLAR LUPOWERTEK FOXESS SMA SRNE

Durable Lithium Battery use CSSUN


Copyright© 2024 CSSUN Energy Co., LTD

BMS Specifications


- Overcharge detection function
- Over discharge detection function
- Over current detection function
- Temperature protection
- Cell Voltage balance function
- Short detection function

Performance Characteristics Data test from 8 Series Cell)


Different Rate Discharge Curve (25°C)




Different Temperature Discharge Curve At 0.5c




State Of Charge Curve At 0.5c (25°C)




Charging Characteristics At 0.5c (25°C)



Cycle Life Curve At 0.2c According DoD



Self Discharge Characteristics Curve



SAFETY WARNING : Use only within the allowed parameters. Do not short circuit or over-load the battery. Charge only using an approved charger designed specifically to charge this battery. Do not heat above maximum temperatures indicated. Never crush, mutilate, puncture or abuse the battery. Do not dismantle the pack or disable any of the protective devices or circuits. Do not use the battery if you suspect it may be faulty or damaged.

Add: Introduction Building, Xingdong Industry Park, Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-29123661 email: sales@cssun.net , support@cssun.net
website: www.cssun.net